

Pre-Consultation Site Plan Application (SPRC)



The undersigned hereby applies to the City of Guelph in accordance with the Planning Act, R.S.O. 1990, C.P.13, as amended, as described in this application, under by-law NO. 2015-19937, as amended

Subject Site

Municipal Address: _____

Legal Description: _____

Registered Owner

Company Name: _____

Contact Name: _____

Email Address: _____

Address: _____

City: _____

Postal Code: _____ Phone Number: _____

Applicant (if different from Owner)

Company Name: _____

Contact Name: _____

Email Address: _____

Address: _____

City: _____

Postal Code: _____ Phone Number: _____

Please select who is the primary contact for this application

Correspondence will only be sent to the primary contact.

Owner

Applicant

Existing Land Use and Property Information

Current Official Plan Designation: _____

Current Zoning: _____ Current Use: _____

Lot Area (m2): _____ Lot Frontage (m): _____ Lot Depth (m): _____

Please select type of application

New Site Plan Application

Amendment to Approved Site Plan

Brief Description of the Proposed Development:

Table 1 Gross Floor Area

	Existing (m2)	New Proposed (m2)
Residential:		
Commercial:		
Office:		
Industrial:		
Institutional:		
Total GFA (m2):		

Existing Number of Residential Units:

Proposed Number of Residential Units:

Is Demolition Required? Yes No

If yes, how much GFA is proposed for demolition (m2):

If yes, how many residential units are proposed to be demolished:

Proposed Building Tenure (Rental, Condominium or Freehold):

Existing Conditions

Are any abutting lands owned by the owner of the subject site? Yes No

Are there any easements affecting the subject site? (All easements must be shown on the site plan) Yes No

Is the site subject to any road widenings? (All road widenings must be shown on the site plan) Yes No

External Agencies

Is the site regulated by the [Grand River Conservation Authority](#)? Yes No

Is the site regulated by the [Ministry of Transportation](#)? Yes No

Is the site within 300m of a rail line (Metrolinx, CN or GJR)? Yes No

NOTE: The City of Guelph does not circulate site plan applications to external agencies (i.e., Canada Post, Alectra, Union Gas, Bell, Rogers, Hydro One, GRCA, MTO, etc.). The applicant is required to contact the various agencies directly to obtain any necessary permits or approvals, and for any site design or coordination works.

Has the site ever been subject to any of the following Development Applications? (Complete table as applicable)

Table 2 Development Application History

	City File Number(s)	Status
Plan of Subdivision		
Zoning By-Law Amendment		
Site Plan Approval		
Minor Variance		
Consent (Severance, etc.)		

Final pre-consultation Site Plan Review Committee (SPRC) summary comments are valid for one (1) year following the pre-consultation meeting date. If a complete pre-submission review or site plan submission is not received within the 1-year timeframe, a new pre-consultation site plan submission will be required.

I hereby apply for pre-consultation site plan and declare that the statements made in this application and the information contained in the accompanying plan(s) are true. I understand that this application does not grant Site Plan Approval and that a complete site plan submission under Section 41 of the Planning Act is required.

Authorized Signature:

Date:

Pre-Consultation Site Plan Submission Checklist

The following materials must be provided digitally in support of a complete pre-consultation site plan submission:

Payment of the [pre-consultation fee](#) by Electronic Fund Transfer (EFT) or cheque. Note: payment must be received before an application is placed on a Site Plan Review Committee (SPRC) meeting agenda

Completed pre-consultation site plan application form including the pre-consultation site plan submission checklist (this document), to confirm all required information is included on each plan

[Section 59 Policy Applicability Review Form](#) in accordance with the Clean Water Act (required for all developments)

Digital (PDF) copy of the following plans:

Site Plan (SP-1)

Building Elevation Plan (EP-1)

Underground Parking Plan(s) (UGPP-1)/ Floor Plans (FP-1) –where parking is proposed underground or within a building/ structure; where common amenity space is required per the Zoning By-law (internal to the building); or where private amenity space is required per the Zoning By-law.

Tree Inventory & Preservation Plan (TIPP-1) – required where wooded features or individual trees greater than or equal to 10 cm DBH may be destroyed or injured.

Preliminary Grading and Drainage Plan (GP-1)

Preliminary Site Servicing Plan (SSP-1)

Any additional available plans

Submissions must be provided via a file sharing program of your choosing (ie. Dropbox [<https://www.dropbox.com>]). A downloadable link must be sent to the Site Plan Coordinator or planning@guelph.ca. If individual PDF attachments are sent via email, we will not accept the submission. Please ensure that the title of the folder includes the municipal address of the proposed development. All digital materials must be formatted/saved in accordance with the City's [Digital Submissions – Document and File Naming Conventions](#) document.

Upon receipt, staff will review your submission to confirm all required information and materials are included. If any required information or materials are not included, the application will be deemed incomplete and will not be circulated/ placed on a SPRC meeting agenda and you will need to resubmit a full submission package for reconsideration.

General Plan Requirements:

- a) All measurements must be in metric.
- b) All plans must be fully coordinated (no conflicting information between plan sets).
- c) Plans must be to an appropriate scale based on the size of the subject lands. The entire site should fit on 1 plan (maximum 2), so the site can be looked at holistically.
- d) Plans must be labelled (drawing title) in accordance with City Naming Protocols:
 - SP-1 – Site Plan
 - UGPP-1, UGPP-2, etc. – Underground Parking Plans
 - FP-1, FP-2, etc. – Floor Plans
 - EP-1, EP-2, etc. – Building Elevation Plans
 - TIPP-1 - Tree Inventory and Preservation Plan
 - GP-1 – Preliminary Grading and Drainage Plan
 - SSP-1 – Preliminary Site Servicing Plan

All plans must include the information in Section 1 within the title block. Furthermore, in addition to the specific plan requirements, all plans (except the building elevation plans, underground parking plans and floor plans), must include all the information in Section 2.

Section 1: The following information must be included in the title block

Drawing title (in accordance with the City Naming Protocol, noted above) i.e. SP-1 – Site Plan.

Municipal address and legal description of the subject lands.

Date of the drawing and version/revision number.

Stamp and endorsement by a Professional (please refer to the specific plan criteria for who is permitted to stamp and endorse the plan).

Metric scale (1:100, 1:200, 1:250, 1:300, 1:400, 1:500) and bar scale.

North Arrow (including construction North).

Note: this does not need to be included on underground parking plans, floor plans or building elevation plans.

Key plan showing the location of the site within the City of Guelph with reference to the nearest intersection of public roads.

Note: this does not need to be included on underground parking plans, floor plans or building elevation plans.

Section 2: The following information must be included on each plan. (Except on Underground Parking Plans, Floor Plans or Building Elevation Plans)

Shown	N/A	Information for the adjacent lands:
		<ol style="list-style-type: none"><li data-bbox="570 470 1422 646">1. Illustrate & dimension the municipal road(s) abutting the subject lands including the existing lane configuration, curbs, sidewalk, bike lanes or bicycle paths, boulevard and/or ditch, sidewalks, bus stops, bus shelters, transit pads, laybys, etc.<li data-bbox="570 688 959 726">2. Adjacent street names.<li data-bbox="570 768 1422 835">3. Location of any existing buildings or structures on the adjacent lands.<li data-bbox="570 877 1422 982">4. Illustrate the location of existing driveways for the adjacent lands, including any driveways opposite the subject lands.

Design Requirement: Where applicable, the centerline of a proposed access must be aligned with the existing access opposite the subject lands (in accordance with the Transportation Association of Canada (TAC) Geometric Design Guide for Canadian Roads). Please illustrate the centerline alignment.

5. Existing & proposed above ground utilities within the City's right-of-way, including fire hydrants, utility poles, guy wires, traffic signalization and equipment, lighting, street signs, transformers, utility pedestals etc.

Design Requirement: A minimum clearance of 1.5m is required from an access to the outside edge of any above ground utility structures. Dimension the setback to any existing or proposed utilities near the existing & proposed access (in accordance with the Zoning By-law and the [City's Development Engineering Manual \(DEM\)](#))

Design Requirement: Refer to the City's [Tree Technical Manual \(TTM\)](#) document for required tree planting offsets from utilities/ features.

Shown **N/A** **Information for the subject lands:**

1. Surveyed property limits including bearings and dimensions.
2. Clear delineation of the limit/ scope of work of the proposed development (required where development is proposed for a portion of the subject lands).
3. Limit of any Natural Heritage Features, Natural Hazards, and buffers (as applicable) including significant woodland, significant wetland, top of bank, watercourse, etc. and reference to the applicable document or source ie. Official Plan, Environmental Impact Study (EIS), Grand River Conservation Authority (GRCA) etc.
4. Identify and dimension any road widening(s) and/or intersection improvement(s), required under Table 5.1 and Table 5.2 of the City's Official Plan.

Note: Where a land dedication is required, all measurements must be from the ultimate property line as the dedication will be required prior to Site Plan approval.

5. Location of all existing & proposed easements including:
 - who the easement is in favour of
 - the instrument number
 - the reference plan number and part(s)

If there are blanket easements, a note must be included confirming the instrument number(s) and who the easement is in favour of.

Note: In accordance with the City's DEM, any required/proposed sewer easements must be a minimum of 5 m wide for one sewer, 6m wide for two sewers in the same trench, and 7.5 m wide for two sewers in separate trenches. Actual width will vary depending on the size and depth of the sewer(s).

6. Existing & proposed buildings and structures (including accessory structures), and any parts of the building which overhang the ground floor including cantilevers, canopies, balconies, etc. (include dimensions for any parts of the building which overhang the ground floor on the site plan).
7. Existing & proposed limits of underground parking structures and ramps (include dimensions/ setbacks on site plan).
8. Existing & proposed above ground utilities within the City's right-of-way, including fire hydrants, utility poles, guy wires, traffic signalization and equipment, lighting, street signs, transformers, utility pedestals.

Design Requirement: A minimum clearance of 1.5m is required from an access to the outside edge of any above ground utility structures. Dimension the setback to any existing or proposed utilities near the existing & proposed access (in accordance with the Zoning By-law and the [City's Development Engineering Manual \(DEM\)](#))

Design Requirement: Refer to the City's [Tree Technical Manual \(TTM\)](#) document for required tree planting offsets from utilities/ features.

9. Snow storage area(s) must be illustrated, or a note must be included on the site plan if snow will be trucked off-site.

Design Requirement: Proposed snow storage areas must not obstruct any accessible routes, required parking spaces and accessible parking spaces (including access aisles), conflict with any existing or proposed landscaping, or conflict with any existing or proposed stormwater management facilities.

10. Illustrate the limits of existing & proposed slopes and berms.
11. Location of existing & proposed stormwater management facilities must be illustrated (i.e. infiltration galleries).

Shown **N/A** **Pedestrian Circulation:**

1. Illustrate existing & proposed pedestrian walkways, sidewalks, pathways, patios, stairs & ramps (including dimensions & materials), within the City's right-of-way and on the subject property.

Design Requirement: Accessible routes must have a minimum 1.50m clear width, the clear width can be reduced up to 1.20m to serve as a turning space where the exterior path connects with a curb ramp in accordance with the Accessibility for Ontarians with Disabilities Act (AODA).

Design Recommendation: Where cars park and can potentially overhang the route, the accessible route should be 2.0m wide. If not possible, curb stops within the parking spaces are to be provided to ensure the accessible route is not narrowed by parked vehicles. Despite the AODA requirement (noted above), the minimum preferred width for all accessible routes is 1.83m.

Design Requirement: Tactile Warning Strip Indicators (TWSIs) must be provided where curb ramps are proposed or where a depressed curb is provided at a pedestrian crossing and at the top of any stairs (in accordance with the AODA).

Design Requirement: Handrails are required on both sides of any stairs. Handrails must terminate in a manner that will not obstruct pedestrian travel or create a hazard (in accordance with the AODA).

Design Requirement: Provide an accessible pedestrian connection from the proposed building to the municipal sidewalk. If there is no existing municipal sidewalk along the frontage of the subject lands, show a logical place where a future accessible pedestrian connection could be provided and label it as such.

Shown N/A Bicycle Parking and Circulation:

1. Illustrate (on all plans), dimension (on the site plan), and specify the number of existing & proposed bicycle short term and long term bike parking spaces at grade and internal to the proposed building (on the site plan) in accordance with the Zoning By-law. Where indoor long term bicycle parking is provided, label on the site plan how visitors/ employees/ residents will access the indoor bicycle parking.

Design Recommendation: Short term (outdoor) bicycle parking spaces should not obstruct any accessible routes. Where multiple buildings are proposed, bicycle parking should be evenly dispersed and provided by each principle building entrance.

Design Recommendation: Indoor bicycle parking should allow for recumbent hand cycle storage. Recommended dimensions for hand cycle storage are 0.65m by 2.0m. The entrance to the indoor bicycle parking should have an automatic door operator, if not lever handles are required.

Shown N/A Vehicular Access, Driveways and Parking:

1. Location of all 0.3m (1') reserves (to determine where any reserves would need to be lifted to provide access to the subject land)
2. Location of existing & proposed access(es). Specify for any proposed access(es): the width, curb radii (in accordance with the City's DEM) and clear throat length (in accordance with Transportation Association of Canada (TAC) Geometric Design Guide for Canadian Roads). For any proposed access(es), illustrate and dimension the clearance from the proposed access(es) to the existing access(es) and intersection (in accordance with the Development Engineering Manual)

Design Requirement: The angle of intersection between a proposed access, and the intersecting roadway should be at 90 degrees, or as near to right angle as practical for the overall safe operation of the site and roadway (in accordance with Transportation Association of Canada (TAC) Geometric Design Guide for Canadian Roads).

Design Requirement: Where applicable, the centerline of a proposed access must be aligned with the existing access opposite the subject lands (in accordance with the Transportation Association of Canada (TAC) Geometric Design Guide for Canadian Roads). Please illustrate the centerline alignment.

Design Recommendation: Where possible, the proposed access should be located on the side street.

3. Location and dimension (on the site plan) all existing & proposed driveways, drive aisles and parking spaces (denoting on the site plan EV parking, accessible parking, access aisle(s) and carpool parking on the plans, where applicable) (label surface material) in accordance with the Zoning By-law.

Design Requirement: Driveways and drive aisle widths are to be designed in accordance with the Zoning By-law and the City's DEM – the City's DEM states: minimum 6.0m wide where no parking is proposed on either side of the driveway/ drive aisle, 6.5m single loaded parking and 7.0m double loaded parking.

Design Requirement: Accessible Parking spaces must be provided and designed in accordance with the Zoning By-law and AODA. The accessible parking count included in the City's [Facility Accessibility Design Manual \(FADM\)](#) is the AODA provincial standard just in a user-friendly format (refer to Section 4.3.12). As per the AODA, Accessible parking must provide the following two (2) types of parking spaces for the use of persons with disabilities:

- Type A, a wider parking space which has a minimum width of 3.4m and signage that identifies the space as "van accessible"; and
- Type B, a standard parking space which has a minimum width of 2.4m.

4. All accessible spaces must have an adjacent access aisle that is 2.0m wide and extends the full length of the parking space. The access aisle must be marked with high tonal contrast diagonal lines. Access aisles may be shared by two (2) accessible parking spaces.

Design Recommendation: The access aisle be provided on the passenger side of a Type A space when a vehicle is pulled in forward (nosed into) the space.

Design Recommendation: Plot at least one EV parking space as an accessible parking space (either Type A or Type B) with a 2.0m access aisle and connecting to an accessible route is strongly encouraged.

Shown **N/A**

Loading Areas and Circulation:

1. Label and dimension (on the site plan) all loading areas (i.e. truck loading areas, garbage collection areas, accessible passenger loading and drop-off areas, move-in & delivery loading areas).

Design Requirement: All vehicles must enter and exit the site in forward motion.

Design Requirement: To facilitate waste collection for all multi-residential developments, the internal road layout should be designed to permit continuous collection without the waste vehicle needing to reverse (other than in the loading zone). Where the requirement for continuous collection cannot be met, a cul-de-sac, "T" turnaround or three-point turn allowance in accordance with the specifications shown in Appendix D of the City's [Waste Collection Guidelines for Multi-Residential Developments in the City of Guelph](#) must be provided.

Design Requirement: To facilitate waste collection for all multi-residential developments, a minimum overhead clearance throughout the property of 4.5m must be provided. The minimum unencumbered vertical clearance for the entire loading area (which is the length of a collection vehicle), must be 6.5m to accommodate front-end collection vehicles.

Shown **N/A** **Waste Collection:**

1. Illustrate the location of all existing & proposed outdoor waste enclosures/ carts (garbage, recycling & organics). Note: for multi-residential developments, carts must be provided for organics to facilitate municipal waste collection.

Design Requirement (for multi-residential developments): Adequate storage volume space must be provided for a minimum of one (1) week for recyclables, organics, and garbage.

Design Requirement (for multi-residential developments): All communal waste containers (in-ground, surface or carts) must be flush with the ground for truck maneuverability, safe tipping and accessibility for all residents or staff.

Shown **N/A** **Traffic Signage:**

1. Illustrate the location of all existing & proposed signage, including:
 - Fire Route/ No Parking signs along the designated fire route (refer to the sign standards within the City's Linear Infrastructure Standards LIS)
 - Stop sign(s) (Ra-1) – Note: all stop signs must be located within the subject lands
 - Accessible Parking Sign(s) (RB-93) and 'Van Accessible' Tab. The 'Van Accessible' tab is to be provided below the RB-93 sign for only the Type A accessible parking spaces (in accordance with the AODA)
 - Multiple Unit Identifier (MUI) sign(s) (where applicable) – Note: MUI signs should be oriented, so they are clearly visible to vehicles entering the subject lands (and further to the requirements set out in the City's Site Plan User Guide)
 - Free-standing permanent & portable signage (including dimensions, where applicable)

Shown N/A Landscaping:

1. General location of existing & proposed soft and hard landscape elements, including: asphalt, shrub and perennial beds, sod, seed mixes, trees and benches (including adjacent rest areas for wheelchair users). Elements to be labelled.

Design Requirement: Benches must have an adjacent level, firm ground surface of at least 0.92m (36 in.) x 1.37m (54 in.) for wheelchair users (in accordance with the AODA).

2. Height and design (material) of all existing & proposed fences and walls (including: boundary retaining walls etc.).

SP-1 - Site Plan

The Site Plan must be stamped and endorsed by a professional (OALA, OAA, OLS, P. Eng or RPP).

In addition to the information contained in Section 1 and 2, the Site Plan (SP-1) must include the information contained in Section 3.

Section 3: Site Plan Requirements:

Shown N/A Information in the Title Block:

1. Name, mailing address, phone number and email address of the property owner.
2. Name, mailing address, phone number and email address of the applicant.

Shown N/A Information for the adjacent lands:

1. Zoning of the adjacent lands (i.e. RL.2).
2. Existing land use of the adjacent lands (i.e. vacant).

Shown N/A Information for the subject lands:

1. Dimensions of all yards and setbacks, including the setback of underground parking (to confirm zoning compliance).
2. Where multiple buildings are proposed on the subject lands, dimension the distance between buildings (to confirm compliance with the Zoning By-law and the Ontario Building Code).
3. Location of all existing & proposed principle and secondary building entrances.
4. Summary Statistics Table, including:
 - Gross Site Area (m²)
 - Existing floor area to be demolished (m²)
 - Gross Floor Area (existing & proposed), including a breakdown of the existing & proposed floor area for different uses (m²)
 - Detailed Parking Calculations (in accordance with the uses proposed and the Zoning By-law-)
 - Quantity and type of bicycle parking spaces proposed (in accordance with the Zoning By-law)
5. Where the subject site has multiple zones that apply to it, show the limits of each zone on the site plan and label them accordingly.
6. Zoning and regulations compliance chart (see Appendix B of the Site Plan User Guide for an example). The chart must include four (4) columns:
 - The zoning regulation
 - The Zoning By-law requirement
 - What is proposed
 - Conforms (Yes/No) column to confirm whether what is proposed conforms with the Zoning By-Law

If there is any site-specific zoning, the zoning and regulations compliance chart must reference these requirements rather than the requirement of the general zone.

7. Where outdoor common amenity space is proposed and is required per the Zoning By-law, the limits of

each proposed outdoor common amenity space must be clearly illustrated/outlined and dimensioned, and the total area (m²) must be noted for each common amenity space (to confirm zoning compliance).

8. Where applicable, illustrate the Approach and Departure Sight Triangles at the proposed access(es), in accordance with the City's DEM and the Transportation Association of Canada (TAC) Geometric Design Guide for Canadian Roads.
9. Illustrate sight line triangles in accordance with the Zoning By-law and the City's DEM.

Design Requirement: No building, parking or structure shall be located within the sight line triangle. Landscaping may be located within the sight line triangle provided it is maintained in such a manner that its height is not more than 0.8m above the level of the travelled portion of the abutting Streets.

10. Where a drive-through is proposed, or alterations to an existing drive-through are proposed, clearly dimension the required queuing spaces up to the first service window (on the site plan). Drive-throughs are to be designed in accordance with the Zoning By-law, the City's Commercial Built Form Standards, and the City's DEM.
11. For commercial and industrial developments, where only a portion of the subject lands form part of the site plan scope, identify and delineate the portion of the property impacted by the proposed development and identify the area (in hectares) in accordance with Section 3. (k)iii. of Parkland Dedication By-law (2022) 20717.

Shown **N/A** **Fire Routes and OBC Requirements:**

1. Label existing & proposed fire department/ siamese connections (if applicable)

Design Requirement: New siamese connections must be located within 3m of a street or access route except that up to 15m will be permitted if the path from the street or access route to the siamese connection is asphalt, concrete or the like which will be kept clear year round.

2. Label existing & proposed fire route(s)

Design Requirement: A minimum 12m centerline radius must be provided along the designated fire route in accordance with the OBC. Dimension the centerline.

Design Requirement: If the fire route is more than 90m long, provide turnaround facilities for any dead-end portion of the access in accordance with the OBC.

3. Clearly indicate all existing & proposed fire hydrant(s)

Design Requirement: Any new fire hydrants are to be located within the City's right-of-way instead of on private property, if the location will satisfy the OBC requirements for protection of the building. If a private hydrant is to be provided as it cannot meet the OBC requirements, provide a dimension between the hydrant and the building which it is to protect. Note that fire hydrants within the City's right-of-way must be independently serviced directly from the watermain, as per City Standards.

Shown **N/A** **Waste Collection:**

1. For multi-residential developments, illustrate the set location of all existing & proposed waste bins/ carts (garbage, recycling & organics) (with dimensions). For units with garages show a typical detail of the set-out location.

EP-1, EP-2, etc. – Building Elevation Plans

Must be stamped and endorsed by Professional (P. Eng. or OAA) or BCIN (where the proposed development is less than 4-storeys high and 600 m2 in building area).

The following Built Form Design Standard and Guidelines should be referenced for the following development types:

- Commercial buildings, please refer to the City’s [Commercial Built Form Standards](#).
- Townhouses and mid-rise buildings, please refer to the City’s [Built Form Standards for Mid-Rise Buildings & Townhouses](#).
- Developments within the downtown, please refer to the City’s [Downtown Built Form Standards](#).
- Buildings within the Hanlon Creek Business Park, please refer to the Hanlon Creek Business Park Urban Design Guidelines.

For sites that have a site-specific Urban Design Brief, the brief together with the applicable built form standards/guidelines will be used to evaluate the development application.

In addition to the information contained in Section 1, the Building Elevation Plan(s) (EP-1, EP-2, etc.) must include the applicable information contained in Section 4.

Section 4: Building Elevation Plans:

Shown	N/A	Plan Requirements:
		<ol style="list-style-type: none"> 1. All building sides/ elevations (north, south, east & west). 2. Where an addition is proposed, or changes are proposed to an existing building, clearly label what is existing and what is proposed. 3. Label (in metric) the width, length and height of the building(s), including the dimensions and height of any major roofs and parapets. 4. Illustrate that any proposed roof top mechanical equipment and elevator cores will be architecturally integrated with the building design or screened. Refer to the Zoning By-law. Provide details including a line-of-sight drawing/perspective to demonstrate these will be completely screened from surrounding public streets.

5. Proposed building mounted municipal address(es) sign and if applicable, commercial signage details including, proposed signage location and dimensions.
6. Recommended all building materials and material colours that will be used be shown.
7. Provide the massing and conceptual design of the proposed building.

UGPP-1, UGPP-2, etc. – Underground Parking Plans and FP-1, FP-2, etc. – Floor Plans

Must be stamped and endorsed by a Professional (P. Eng. Or OAA)

In addition to the information contained in Section 1, the Underground Parking Plans(s) (UGPP-1, UGPP-2, etc.) and Floor Plans (FP-1, FP-2, etc.) must include the applicable information contained in Section 5, and Floor Plans must include the additional applicable information contained in Section 6.

Section 5: Underground Parking and Floor Plan Requirements:

Shown	N/A	Site Circulation – Vehicular Access and Parking
--------------	------------	--

1. Specify parking ramp slope(s) (in percentage).

Design Requirement:

- Covered ramps should have a maximum slope of 15%
- For any steep ramp, transition areas at the top and bottom of the ramp should be at least 6m in length with half of the ramp grade
- Ensure provision of sightlines at entrance/exit
- Where the ramp is exposed to weather, provide a heated ramp when the slope is greater than 8%

2. Specify vertical clearance (in meters).

Design Requirement: Refer to loading vertical clearance requirements set out in Section 2, where loading areas are proposed within the building limits.

3. Provide the horizontal and vertical profiles for any underground parking structures and ramps.

4. Dimension all driveways, drive aisles and parking spaces. Refer to driveway, drive aisle & parking design requirements set out in Section 2.

Design Recommendation: provide a 1.20 metre hammerhead for end parking spaces abutting a wall.

Shown **N/A** **Indoor Bicycle Parking**

1. Where indoor bicycle parking is proposed, provide details of the bicycle room(s) layout including:
 - Type of bicycle parking proposed (i.e. vertical, horizontal, stacked & accessible/ recumbent bicycle parking) – label on plan(s)
 - Typical dimension for each proposed type of bicycle parking space (length, width & height)
 - Dimension of the access aisle(s) (width)
 - Width and type of door access
 - the total number of bicycle parking proposed for each type of bicycle parking

Refer to the Zoning By-law for bicycle parking requirements.

Design Recommendation: Indoor bicycle parking should allow for recumbent hand cycle storage. Recommended dimensions for hand cycle storage are 0.65m by 2.0m. The entrance to the indoor bicycle parking should have an automatic door operator, if not lever handles are required.

Shown **N/A** **Traffic Signage:**

1. Location of proposed traffic signage:
 - Stop sign(s) (Ra-1)
 - Accessible Parking Sign(s) (RB-93) - 'Van Accessible' Tab to be provided below the RB-93 sign for Type A accessible parking spaces (in accordance with the AODA)

Shown N/A Loading Areas and Waste Collection

1. For all multi-residential developments, where waste storage is proposed internal to the building, provide details of the waste storage area, including:
 - The waste stream (organics, garbage, or recycling) for each proposed bin/cart
 - size/volume for each proposed bin/cart
 - dimensions of the proposed bins/carts

Note: Carts must be provided for organics to facilitate municipal waste collection.

Design Requirement: Adequate storage volume space must be provided for a minimum of one (1) week for recyclables, organics, and garbage.

Section 6: Additional Floor Plan Requirements:

Shown N/A Amenity Areas:

1. Where indoor common amenity area(s) are proposed and are required per the Zoning By-law, the total area (m²) must be noted for each common amenity space (to confirm zoning compliance).
2. Where private amenity areas are required per the Zoning By-law, the private amenity spaces must be fully dimensioned, and the total amount of private amenity space proposed for each unit (m²) must be specified (to confirm zoning compliance).

TIPP-1, TIPP-2, etc. – Tree Inventory and Preservation Plan(s)

Must be prepared by an arborist.

Refer to the City's [Tree Technical Manual \(TTM\)](#) for plan requirements.

In addition to the information contained in Section 1 and 2, the Tree Inventory & Preservation Plan(s) (TIPP-1, TIPP-2., etc.) must include the information contained in Section 7.

Section 7: Tree Inventory and Preservation Plan Requirements:

Shown	N/A	Plan Requirements:
--------------	------------	---------------------------

1. A surveyed inventory of all existing trees (10cm Diameter at Breast Height (DBH) or larger) on the subject lands, and those on adjacent lands where the dripline is within 6m of the subject lands, that are to be preserved, injured or removed.
2. A tree inventory table which includes the following:
 - identification number (corresponding to the plans)
 - size of tree - Diameter at Breast Height (cm)
 - species (common and botanical name)
 - form (canopy width, shape, etc.)
 - biological health (disease, pest, vigour)
 - structural condition (hazards and/or structural defects)
 - tree ownership (private or public)
 - recommended action (retain, relocate or remove)
 - compensation required (yes or no)
 - reason for removal (health, development, hazard, etc.) or relocation, if proposed
 - risk assessment
 - overall condition (considering biological health and structural condition)
 - Identification of Designated Heritage Trees protected under the Ontario Heritage Act (OHA)
 - Notes and recommendations as applicable (e.g. treatments, vine removal, habitat tree, corrective pruning, etc.)
3. Location and description of the type of tree protection fencing and other tree protection measures (e.g. wood fence, paige wire fence, root pruning, sensitive excavation, compaction prevention, etc.). Including notes and appropriate Tree Protection Zone (TPZ) Fence details and drawings in accordance with the City's TTM.

GP-1 – Preliminary Grading and Drainage Plan

Must be stamped and endorsed by professional (P. Eng.)

Refer to the [City's Development Engineering Manual \(DEM\)](#) for grading design requirements.

In addition to the information contained in Section 1 and 2, the Preliminary Grading Plan (GP-1) must include the information contained in Section 8. The City is looking for enough information to determine the cut/fill.

Section 8: Preliminary Grading and Drainage Plan Requirements:

Shown	N/A	Plan Requirements:
		<ol style="list-style-type: none">1. Geodetic Benchmark.2. Location of all existing trees (10cm DBH or larger) on the subject lands, and those on adjacent lands where the dripline is within 6m of the subject lands, that are to be preserved.3. Proposed erosion and sediment control measures (coordinated with required Tree Protection Fencing may be required).4. Provide the existing road centerline and top of curb elevations for the municipal right-of-way at 20m intervals.5. Location of all existing & proposed curb cuts/fills within the municipal right-of-way.6. Existing and proposed contours at 0.5m intervals over the entire development and sufficient area of adjacent lands to establish the overall drainage pattern.7. Directional arrows illustrating surface drainage flow for the subject lands and the adjacent lands.

8. Location and height of existing & proposed boundary retaining walls by showing top of wall (T/W) and bottom of wall (B/W) grades. Width of proposed retaining wall to be shown on a detail.

Design Requirement: All proposed retaining walls must be located on private property with a minimum setback of 150mm to the property line from the base of the retaining wall in accordance with the City's DEM.

9. Finished floor, underside of footing and basement floor elevation for any proposed buildings and/ or structures.
10. Location of existing & proposed roof water leader discharge points.
11. Location of existing & proposed swales, ditches, culverts & channels.
12. Location of existing & proposed catch basins.

SSP-1 – Preliminary Site Servicing Plan:

Must be stamped and endorsed by Professional (P. Eng.)

Refer to the [City's Development Engineering Manual \(DEM\)](#), [Linear Infrastructure Standards](#) and [Design Guidelines and Supplemental Specifications for Municipal Services \(DGSSMS\)](#) for site servicing design requirements.

In addition to the information in Section 1 and 2, the Preliminary Site Servicing Plan (SSP-1) must include the information contained in Section 9.

Section 9: Preliminary Site Servicing Plan Requirements:

Shown	N/A	Plan Requirements:
--------------	------------	---------------------------

1. Location of individual trees, vegetation units (10 cm DBH or greater) on the subject property, and existing trees (10cm DBH or greater) on adjacent lands where the dripline is within 6m of the subject lands, per the requirements of the City's TTM, that are proposed to be retained.

2. Existing and proposed watermain, sanitary and storm sewer infrastructure within the City's right-of way and within the subject lands (including size).
3. Existing and proposed maintenance holes, catch basins, water valves, water meters and fire hydrants within the City's right-of way and within the subject lands (including sizing information).

Design Requirement: any new fire hydrants are to be located within the City's right-of-way instead of on private property, if the location will satisfy the OBC requirements for protection of the building. Note: fire hydrants within the City's right-of-way must be independently serviced directly from the watermain, as per City Standards.

Design Requirement: All water including that to supply fire suppression and hydrants within private property (where the water service line is 4" (100mm) or greater) must be bulk metered. The bulk water meter must be located within a meter chamber at the property line if the distance from property line to point of entry of the water service to the building is greater than 30m or a mechanical room designed to house and facilitate installation of required meter will be permitted if this distance is less than 30m. No tee fitting or connections are permitted prior to the water meter.

Design Recommendation: Maintenance holes and catch basins should not be located along accessible routes or within accessible parking spaces including 2.0m behind accessible parking spaces.

4. Location of existing & proposed swales, ditches, culverts & channels.